

Vandal Proof Mini Speed Dome Camera Model: YPTZ



We now offer this awesome high quality vandal proof mini speed dome. This unit is about half the size of a conventional speed dome so it looks great indoors or out. On the ceiling it can be mounted flush or recessed into the ceiling. It has an optional wall bracket to allow wall mount. This unit will pan, tilt, or zoom up to 100X (total zoom = optical zoom X digital zoom). Great choice with the OptiView DVRs.

Notes:

1. To use a PTZ camera on our PC Based DVRs, you must have an RS485 Converter.
2. Color shows here (with wall mount) is more indicative of camera true color (off white).



Mini PTZ with Optional Wall Mount

Product Includes

- Ceiling bracket
- Power supply
- Installation / Instruction Manual
- Wall bracket is optional

File Name: color speed dome camera manual.pdf

Size: 2568 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 20 May 2019, 16:21 PM

Rating: 4.6/5 from 769 votes.

Status: AVAILABLE

Last checked: 6 Minutes ago!

In order to read or download color speed dome camera manual ebook, you need to create a FREE account.

[**Download Now!**](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with color speed dome camera manual . To get started finding color speed dome camera manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

color speed dome camera manual



Please choose a different delivery location. Our payment security system encrypts your information during transmission. We don't share your credit card details with thirdparty sellers, and we don't sell your information to others. Please try again. Please try again. Please try your search again later. To calculate the overall star rating and percentage breakdown by star, we don't use a simple average. Instead, our system considers things like how recent a review is and if the reviewer bought the item on Amazon. It also analyzes reviews to verify trustworthiness. **WARNING** This symbol is intended to alert the user to the presence of uninsulated dangerous voltage. **CAUTION** This symbol is intended to alert the user to presence of important operating and maintenance Servicing instructions in the literature accompanying the appliance. This symbol on the product or on its packaging indicates that this product shall not be treated as household waste. Instead it shall be handed over to the applicable collection point for the recycling of electrical and electronic equipment. By ensuring this product is disposed of correctly, you will help prevent potential negative consequences for the environment and human health, which could otherwise be caused by inappropriate waste handling of this product. The recycling of materials will help to conserve natural resources. For more detailed information about recycling of this product, please contact your local city office, your household waste disposal service or the shop where you purchased the product. Do not install the product in an environment where the humidity is high. Unless the product is waterproof or weatherproof, otherwise poor image quality may occur. Please take extreme care when cleaning the dome surface. The plastic material that the dome is made of is, by necessity, relatively soft and prone to nicks and scratches which will impair vision through the dome. <http://primary-insulation.com/userfiles/esec-2008-manual.xml>

- 1.0.



Do not plug and unplug the power cord, it may result product malfunction. Make sure to use only the power source specified in the specification. Before operation, please make sure that the product has been properly installed. 2 4 2. Symbol Description 1. Function keys are shown by, framed capital boldface print letters. Example ENTER meaning, press the function key 2, 8, and then ENTER. Auto Iris and Manual Iris Control. Wide Dynamic Range Function, able to reveal dark and bright video images option. Digital Noise Reduction function, to inhibit AGC noises under low lux option. Motion detection function, the screen detects moving objects and sends Alarm signals option. Automatic tracking Auto Tracking function detects moving objects and automatically follows the object on the screen option. Mask PTZ Mask, 4 Area instant privacy screen mask option. Cruise track PATTERN, achieve cruise control of the SPEED DOME by setting up preset cruise points total setup of 4 groups. Preset automatic swing cruise, group mode, auto cruise mode and circling mode. Horizontal Rotation of 180. Built in 5 Alarm Inputs and 2 Relay Outputs Relay type and open collector type. Selectable alarm out signal NO Normal Open or NC Normal Close and ALR OUT Open Collector Type. Remote Control via RS485. Connects up to 255 Speed Dome Cameras. Supports PELCO Protocol D and P Protocol. Indoor Type Power Input DC12V Outdoor Type Power Input AC24V or DC12V. Builtin heater and fan to maintain camera in normal operating temperature for outdoor type only. Suitable for installation on different occasions Indoor Type can be flush mounted on a ceiling or in the ceiling with only the dome showing. Control keyboard can connect up to 32 subsystems to form one control system. Using the main control keyboard, each system can be controlled separately. Push the joystick anticlockwise, for far away image widen the angle of viewing and release the joystick to stop zooming. <http://www.geconte.pt/fotos/esdm-manual.xml>



Joystick Control The movement depends on the angel of the joystick the more you push the joystick, the faster the speed Push the joystick up or down, the device will move forward or backward. Push the joystick left or right, the device moves leftward or rightward. Under zoom mode, the speed movement becomes slow. 17 19 FOCUS CONTROL Press FOCUS FAR focus far and release the key

to stop focusing. Press FOCUS NEAR focus near and release the key to stop focusing. CALL PRESET POINT Type the preset point number on the keyboard, press GO PRESET button GO PRESET XXX and the LCD screen will display. Then the color Speed Dome camera will move to the specified position. Press Key number 1 and go preset, to setup Preset Position number 1. Press GO PRESET button. Press Key number 28 and go preset, to setup Preset Position number 20 10. Auto Select auto mode to enable automatic adjustment of the focus position. Push Auto Select push auto to adjust focus position TELE or WIDE, the preset value becomes AF mode and returns to Manual Focus mode. DISTANCE This function is applied for setting up the minimum shooting distance. Set the Focus Distance mode to 1.5M, 3M, 5M or 10M Default 1.5M. ZOOM START Set the Zoom Start mode from x1 to x35. ZOOM END Set the Zoom End mode from x2 to x576. ZOOM SPEED Set the Zoom Speed to slow, normal or high. CENTER BRIGHTNESS Set the brightness affect of image display. Switches to Color when Night Day AE Value Default Setup 63. Return to default setup. PUSH AUTO PUSH AUTO ON Enable auto tracing white balance. PUSH AUTO OFF Disable auto tracing white balance and record the current white balance value. SYNC When using a DC 12V adaptor, the sync setting is set to internal sync Default Setup INT and to linelock sync when using an AC 24V adaptor. Return to default setup. 28 30 10.7 PRIVACY MASK The purpose of the applying privacy mask function is to cover up specific areas on the screen display to achieve the purpose of privacy protection.

Four sets of privacy masks can be setup. EDIT Please see the setting as below to edit privacy mask area 1. Under main menu, enter Privacy Mask function setup page. 2. Move the joystick of the keyboard to item EDIT and press OPEN button MASK function will be set to OFF status after entering EDIT mode. 3. Enter EDIT mode, a cross appears in the center of the display. Use the keyboard to control the joystick and setup the mask area. Press OPEN button to confirm and CLOSE to cancel setup. 4. The system auto returns to privacy mask setup page after setup is successful. TILT angle of 76 degrees to 90 degrees can not be set as MASK. Return to default setup. 29 31 10.8 MOTION DETECT The purpose of applying privacy mask function is to cover up specific areas on the screen display to achieve the purpose of privacy protection. Four sets of privacy masks can be setup. For more information on preset point, please refer to Pg.18. AE TYPE The Speed Dome can setup three different parameters to combine with the Preset application, and select the PROFILE on PRESET POINT menu. When swing function runs, camera moves from the preset assigned as the 1st point to the preset assigned as the 2nd point in CW Clockwise direction. The Auto Swing function has a total of 4 setting groups. The higher the value, faster the speed EXEUTE Execute the preset function Return to default setup. Each group is allowed to set up 32 preset points for moving speed and retention time. The Auto Pan has a total of 4 setting groups. MOVE SPEED Adjust the move speed, and the higher value means the faster speed. DWELL TIME sec The speed dome stop the point time after execute the function EXEUTE Execute the function Return to default setup. EXAMPLE If you wish to set only 4 preset points, you must set the 5th preset point to 0. The system will auto pan as follow Example 1,2,3,4,0. Start Group Cruise 1. To activate preset group, select GROUP SETUP item under camera function setup page.



This feature can store up to four sets of cruising tracks. DWELL TIME sec The point of time after the speed dome execution stops. EDIT Setup the CRUISE function; please refer to Setup Steps illustration. EXECUTE Precede cruise function. Move the keyboard joystick controller and plain your cruise path, when the screen displays 100% memory capacity indicates that the memory is full and can not continue to record cruise tracks. Start Auto Cruise 1. To activate auto cruise preset group, select CRUISE SETUP item under camera function setup page. User can setup the menu rotation direction and rotate speed to determine its direction and speed. This feature can store up to four sets of circling cruise. SPEED Adjust the move speed, and the higher value means the faster speed. Start Circling Mode 1. To activate circling preset group, select CIRCLING SETUP item under camera function setup page. TIME The function will enable after the RETRUN TIME. ACTION INDEX It means all ACTION NUM values IDLE TIME It is the recovery waiting time of AUTORUN. MOTION ALARM Enable the Alarm out after motion detection. To enable alarm function when MOTION occurs, setup MOTION ALARM to ON. 5. Use the joystick on the control keyboard, move to item TIME and setup the return time of the autorun it is the period of time when the joystick is not in operation till the time of system autorun. 6. Exit MENU mode. 7. Do not use the keyboard, wait for the TIME and start AUTORUN. The device will move to the specified PRESET position. When an object moves, MOTION becomes triggered. Message M and AO appears on the screen and changes the output status of RELAY and OPEN COLLECTER. Until there s no object movement, the message M and AO will disappears on the screen. RELAY output status will switch to NORMAL OPEN, OPEN COLLECTER will return to setup mode during ALARM SETUP output status.

<http://atmos-service.com/images/car-body-repair-manuals.pdf>



Tips MOTION ALARM in the menu option must be set to ON, to enable an AO message to appear when a MOTION event occurs, and to change the output status of RELAY and OPEN COLLECTER. 43 45 Setup Steps Tracking The main purpose of the Tracking mode is to aim and follow the largest movement or moving object in the monitoring screen. When tacking mode has been setup while the system enters Auto Run mode, the system will auto startup tracking mode. The device will move to the specified PRESET position. Factory default settings are as shown below ALARM SETUP ALARM NUM SENSOR 1 ALARM SWITCH OFF ACTION TYPE PRESET PRESET MODE 5 SEC ACTION INDEX 1 CYCLE INDEX NA OPEN COLLECTOR LOW OFF ALARM NUM Five selectable Menu options SENSOR1, SENSOR2, SENSOR3, SENSOR4 and SENSOR5. ALARM SWITCH Each sensor can be switched ON or OFF by using the joystick on the keyboard. ACTION TYPE Select the action mode when a sensor has been triggered. There are five types of sensor modes PRESET, SWING, CRUISE, GROUP and NONE. When switched to a certain mode, the corresponding item PRESET MODE, ACTION INDEX and CYCLE INDEX will be switched to the corresponding options. PRESET MODE Desired preset operation mode is selectable only when the ACTION TYPE is set to PRESET. Tracking Options When an alarm occurs, system will start the tracking function. When the object moves, the camera will automatically start tracking the object. 45 47 ACTION INDEX Select the action number of the desired action operating mode, when the alarm SENSOR1, SENSOR2, SENSOR3, SENSOR4 or SENSOR5 occurs, the selected action number will start the corresponding action. When the ACTION TYPE is set to NONE, NA will appear on the ACTION INDEX and no

preset points can be selectable. If you select one of the options PRESET or NONE within the ACTION TYPE, NA will appear in the CYCLE INDEX option. When an alarm alert occurs, the system will initiate the action mode previously set.

<http://atonenergia.com/images/car-cd-manual-eject.pdf>



Example When 3 CYCLE has been setup, it means the action mode will perform 3 times and then stop. When the HOME setup of the AUTORUN function has been set to ON, wait for the TIME to end, the system will implement ACTIVE TYPE of the AUTORUN setup. When the alarm has been triggered, it will trigger the output contact and switch to the opposite user setup value. When the time setup option in the PRESET MODE has been complete, the time trigger alarm of the alarm output contact will switch back to user setup page under alarm setup status.

Appendix Trouble shooting

1. Speed Dome Camera switched OFF Check whether the power supply is correctly connected Indoor Type DC12V Outdoor Type DC12V or AC24V. Check whether the fuse has been burned. Check whether or not the 20PIN the camera foot has fallen off. Check whether or not the outdoor type 2PIN power cable has fallen off.
2. No video image on the monitor Check whether the video signal line of the Speed Dome Camera is connected properly. Check whether video signal has been disconnected. Check whether the video signal line of the monitor is connected properly. Check whether the 20PIN of the Speed Dome Camera has fallen off.
3. Unable to control the Speed Dome Camera Check whether the ID position is correct. Check whether the communication control terminal RS485 JACK and control wire is properly connected. Please disable Auto Pan Function. Check whether the Speed Dome Camera is in the act of processing the alarm due to alarm interchange action. For this eliminates all functions.
4. Speed Dome Camera Out of Focus Please wipe with cottoncloth when there are dusts on the transparent cover or on the Speed Dome Camera Housing. Horizontal rotation of 180 single bond 300 Per Sec.

Operation is subject to the following two conditions 1 this device may not cause harmful interference, and 2 this device This manual is applicable to DS2CC102PNIR1IR3IR5, Before operating this product, please read this instruction manual carefully to ensure OnScreen Display OSD Menu Please read this User s Manual before using the product. Change without Notice AWT07MLED 7 Q TFT LCD MONITOR LED Backlighting USER MANUAL e4 SAFETY PRECAUTIONS Federal You made the right decision in choosing HIKVISION disclaims any liability High Sensitivity, 0.06 If there are any questions, or requests, If there is any question or request, please do not hesitate to contact dealer. This manual is applicable to Check the package contents against the list below. See P.1 Physical A ISSUE DATE REVISIONS A July 2004 Initial Release PCN 1752. Rev. A ii

MXMU000933 FCC COMPLIANCE STATEMENT INFORMATION TO THE USER Warning! High voltage the electrical Do not connect it to March 2015 CAM6500 series. Ver. 070307. Quick Installation Guide This product employs integrate circuits, low power consumption, and no radiation Call Us Toll Free 18005350104 Fax 7403660771 Website www.holtzindustries. Think RayView! A Division Of Holtz Industries, Inc. We Offer Full Systems, Monitors, Cameras and Accessories We Accept These Major Credit Cards ONBACK Call For Safety s Sake Your If there are any questions, or requests, please do not hesitate to contact the dealer. This manual applies to Factors to consider when selecting your video surveillance cameras You have many assets to protect so you Please keep User Guide for future reference. Please read the cautions to prevent possible danger The company reserves the right to revise Need Some Help This manual should help you understand your new product. If you still have questions, call our help line found on the insert If there is any question or request, please do not hesitate to contact dealer.

<http://slowjamsundays.com/wp-content/plugins/formcraft/file-upload/server/content/files/16283c1fcbdc7c---bt-response-75-answer-machine-manual.pdf>

This manual is applicable The distorted hemispherical image of the fisheye camera will be converted Retain this Owner s Manual for future reference. User Guide All rights reserved. Operation Manual Please read carefully and follow all warnings and instructions in Please save this manual for future reference. To use this website, you must agree to our Privacy Policy, including cookie policy. User's Manual Chapter 2 Structure. 5. Chapter 3 Dome Settings. 7. Chapter 4 Installation Guide. 10. Chapter 5 Functions Description. 13 Chapter 6 Operation instruction. 18 In transportation and storage process, we need to prevent stress, such as Damage caused by assembled Handle the product carefully and gently. Prevent such incorrect operations as Under the cover are advanced optical devices, avoid direct hand touch, for the The electrical installation must comply with safety standards, with use of Control signals and video signals should maintain a sufficient distance from Keep power off until the Do not dismantle internal parts, please turn to qualified maintenance Make sure that there is no metal object or flammable materials inside the Be careful to If the product is placed near TV, radio transmitters, electromagnetic devices, It is advised to avoid collision or vibration. Do not use strong or abrasive When cleaning up dirt, use dry cloth. if dirt is If there is sticky dust on the lens, Power. Communication port Moisture Move the cursor to EDIT and press IRIS ON to enter edition mode. Move the There are up to 32 presets in a single E1. Delete. Move cursor to "delete", press Iris On to delete related sequence. Then the sentence "PRESS IRIS ON TO CONFIRM" will Move the joystick and press IRIS ON to confirm. These functions include presets, cruising track, pattern Mover the cursor to the time duration to be set, and press " Iris Open" to Press IRIS ON to enable or disable the timing action Note.

The settings of each time periods can not overlaid, and the time period can not If the use tries to control the dome during the TIMING ACTION, then the Sensitivity of auto tracking funtion. Scale from 1 Operation is subject to NOTE This equipment has been tested and found to comply with the limits These limits This equipment generates uses and can radiate radio frequency energy and, However, there is no Reorient or relocate the receiving antenna. Increase the separation between the equipment and receiver. Connect the equipment into an outlet on a circuit different from that to PDF Version 1.5. Linearized No. Page Count 44. Language zhCN. Tagged PDF Yes. Title IR HIGH SPEED DOME CAMERA. Author User. Learn more at privacy policy. August 1 Dominique ALLAIN September 26 giuliano milini Show next reviews 4.5 1080P HD PTZ IP Camera Wifi Outdoor Speed Dome Wireless Wifi Security Camera Pan Tilt 4X Digital Zoom 2MP Network CCTV Surveillance from Price RUB 3,769 rub. Specification. Product Name Wifi Camera. Mode C36789. Pixels 2.0MP. Waterproof Grade IP66. Lens 3.6MM. Electronic Shutter Auto. IR LED 4pcs LED lights and 6pcs Infrared Array. Night Vision IRCUT automatic switchover, 2530M differ from environment. Alarm Motion Detection, Alarm picture push. ONVIF Support. Storage Support TF Card Max 64G .

Shell Plastic Weatherproof case, Protection grade. Feature August 1 Dominique ALLAIN September 26 giuliano milini Show next reviews Warranty We will refund your money if product was not delivered within 70 days after purchase. You have 2 weeks to request refund — up to 84 days. Product doesn't match the description. Contact us within 30 days after you receive it. In case of cancellation, money will be refunded to your account within 14 days. Similar items 24% Price RUB 2,848 rub. HD 1080P WiFi Wireless CCTV PTZ IP Camera Audio Home Security Night Vision Waterproof Weatherproof 24% Price RUB 3,096 rub.

1080P HD PTZ IP Camera Wifi Outdoor Speed Dome Wireless Wifi Security Camera Pan Tilt 4X Digital Zoom Home Garden 21% Price RUB 4,077 rub. 1080P HD Outdoor Waterproof WiFi PTZ Pan Tilt Home Security Smart IP IR Camera 20% Price RUB 3,830 rub. Vstarcam 4X Zoom WIFI IP Camera HD 1080P Wireless PTZ Dome CCTV IR Outdoor Security Surveillance Cam 23% Price RUB 3,165 rub. Mayitr Wireless 5X ZOOM CCTV HD 1080P WIFI IP Camera Outdoor Home Security IR Cam 40% Price RUB 1,483 rub. Outdoor Waterproof HD CMOS 1000TVL 36 LED IRCUT Cylinder CCTV Security Cam 45% Price RUB 1,361 rub. Wireless Mini WIFI IP Camera HD 1080P Smart Home Security Camera Night Vision AD 18% Price RUB 4,095 rub. 1080P HD Camera 5X Zoom WiFi Wireless Security Surveillance Outdoor Night Vision Recording Camera AD 19% Price RUB 6,772 rub. PIR Body Induction 2.8MM HD Outdoor Solar Powered Wireless WIFI IP Surveillance Security Camera Night Vision Support MICRO SD Card AD 18% Price RUB 4,549 rub. FLOUREON 1080P 2.0MP 3000TVL PAL Waterproof Outdoor CCTV DVR Security Camera Night Vision Cam 53% Price RUB 900 rub. 1400A Fake Dummy Camera Bullet Security CCTV Surveillance Camera Silver 30% Price RUB 2,174 rub. HD720P Security Home Wireless WIFI IP Outdoor IR Night Vision Motion Camera 21% Price RUB 2,764 rub. AUGIENB 6LEDS HD 1080P Outdoor Night Vision Surveillance Wifi IR IP Camera Waterproof 200W Pixel Monitor Home Security Support 5 Users 48% Price RUB 953 rub. Durable 24 LED Light Dome Night Vision 3.6mm Lens HD Camcorder Indoor Camera AD 19% Price RUB 5,302 rub. 4X Zoom Outdoor HD 1080P PTZ WIFI IP Camera IP66 Waterproof 50M Night Vision Surveillance Home AD 32% Price RUB 1,934 rub. AUGIENB Wireless IP Camera HD 1080P Mini Wifi Camera Network P2P Baby Monitor CCTV Security Video Camera with IRcut Two Way 20% Price RUB 4,018 rub. 1080P Wireless PTZ Pan Tilt 2MP Fullcolor Night Vision Dome 2Way Audio Security WiFi CCTV Camera 18% Price RUB 4,312 rub.

5X Zoom Optical WiFi Camera HD 1080P 2MP PTZ IP IP66 FullColored Night Vision Outdoor Wireless Smart Home Security Surveillance Audio Motion 52% Price RUB 786 rub. 1200TVL 3.6mm 24LED Outdoor Waterproof Security IR Night Vision CCTV Camera AD 19% Price RUB 4,463 rub. Drillpro IP Camera Security Monitor HD 1080P WIFI PTZ IP66 Speed Dome Wireless 200W 7LED 4X Optical ZOOM AD 21% Price RUB 3,037 rub. 1080P HD Camera Dual Light Source Lamp WIFI Network Camera Outdoor Wireless Waterproof Night Vision TF Card Camera 19% Price RUB 3,488 rub. HD 1080P Outdoor Camera Surveillance Camera Wifi IR IP Camera Waterproof 200W Pixel Monitor 8 LEDES AD Brand Price RUB 7,015 rub. DID 4CH 1080N HDMI DVR Recorder HD IR 1080p Outdoor Home Security Camera System 23% Price RUB 2,875 rub. 1080P HD PTZ Security WIFI Camera Outdoor Dome Wireless IP Camera 4X Zoom IR Network Surveillance AD 22% Price RUB 4,442 rub. HD 1080P 8 LED Wireless IP Camera Pan Tilt Zoom Wifi Surveillance Home Security AD 29% Price RUB 2,038 rub. 1080P IP Camera Wifi Home Security Camera Support P2P Phone Remote Control IRCUT Filter Infrared AD 18% Price RUB 6,244 rub. Security Outdoor Camera 1080P IP Camera Wifi Infrared Monitor Night Vision Support Motion Detection AD 23% Price RUB 3,625 rub. Waterproof 8 LED 4x Zoom 2.0MP PTZ Pan Tilt HD 720P Speed Dome Camera Security 200W Pixel Monitor IP Twoway Audio WiFi Night Vision Automatic IRCUT Show more Best prices for 1080p hd ptz ip camera wifi outdoor speed dome wireless wifi security camera pan tilt 4x digital zoo You can buy 1080p hd ptz ip camera wifi outdoor speed dome wireless wifi security camera pan tilt 4x digital zoo in the Joom online store at a good price. The product has a large description, high quality photos, specifications, customer reviews and accessories. Get Latest Price from the seller We have

continued to provide components and devices that have contributed to industrial development worldwide.

To meet the demands of the market and changing market conditions, the determining factors will be our strengths in technological development and products. In addition to consumer, education, enterprise, government and creative markets, the company provides hardware products and solutions for customers in the information technology and scientific markets. At present, we are committed to providing interactive white board solution in the fields of finance, telecommunication, industrial control, medical treatment, education all over india and our product range covers interactive whiteboard, wireless presenter, wireless tablet, digital visualizer, voting system,central control system etc.Get Best Deal I agree to the terms and privacy policy All rights reserved.

<https://events.citeve.pt/chat-conversation/boss-bass-chorus-ceb-3-manual>